



Model NO.		IPDA20G200	IPDA20S400	IPDA20S500	IPDA20G500	IPDA20NT4K
Video	Chipset	IMX307+GK7205V200	SC401AI+NT98562	SC5239S + GK7605V100	IMX335+GK7205V300	SC8239+NT98566
	Image Sensor	1/2.8" SONY Sensor	1/3" CMOS Sensor	1/2.8" CMOS Sensor	1/2.8" SONY Sensor,	1/2.7" CMOS Sensor
	Resolution	2MP	4MP	5MP	5MP	8MP/4K
	Main Stream	2MP@20fp 720P@30fps	4MP@25fps 3MP@25fps 1080P@25fps	5MP@20fps 4MP/3MP@25fps 1080P@25fps	5MP@20fps 4MP/3MP@25fps 1080P@25fps	8MP@15fps 5MP/4MP25fps 1080P@25fps
	Compression	H.264/H.265				
Main Features	Day/Night	Color/B&W(IR-CUT)				
	Defog Mode	Support				
	Lens	Board Lens 3.6mm/F2.0 (2.8mm/6mm lens Optional)				
	IR LED	3pcs				
	IR Range	20m				
	Resolution	4K/5Mp/4Mp/2Mp				
	Motion Detection	Support				
	Human Detection	Support				
	Mobile Alert Notification	Support				
	Recording Mode	NVR/CMS/WEB				
	Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Nederlands				
Ineterface	Audio	Audio input/output Optional				
	Alarm	/				
	SD Card Slot	/				
	RS485	/				
Network	Ethernet	RJ45				
	Protocols	TCP/IP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP, NTP,UPnP,SMTP,IPv6,et				
	Onvif Protocol	Yes				
Compatiable with		XMEYE APP, NVR, NAS, Live Stream to 3rd party Using RTSP				
Others	Power	12V DC (Dual Voltage DC12V/AC24V Optional)				
	POE	Optional				
	Housing	Metal IP66				
	Humidity	10-85% RH				
	Operation Conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F)				
	Weight	400g				
	Product Size	Φ110×90mm				