



Model NO.		IPDQ30G200	IPDQ30G500	IPDQ30NT4K
Video	Chipset	IMX307+GK7205V200	IMX335+GK7205V300	SC8239+NT98566
	Image Sensor	1/2.8" SONY Sensor	1/2.8" SONY Sensor,	1/2.7" CMOS Sensor
	Resolution	2MP	5MP	8MP/4K
	Main Stream	2MP@20fp 720P@30fps	5MP@20fps 4MP/3MP@25fps 1080P@25fps	8MP@15fps 5MP/4MP25fps 1080P@25fps
	Compression	H.264/H.265		
Main Features	Day/Night	Warm Light Full Color		
	Defog Mode	Support		
	Lens	Board Lens 3.6mm F1.0 (2.8mm/6mm lens Optional)		
	IR LED	4pcs Warm White Lens		
	IR Range	20m		
	Resolution	4K/5Mp/4Mp/2Mp		
	Motion Detection	Support		
	Human Detection	Support		
	Mobile Alert Notification	Support		
	Recording Mode	NVR/CMS/WEB		
	Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands		
Ineterface	Audio	Audio input/output Optional		
	Alarm	/		
	SD Card Slot	External SD Card Slot Optional		
	RS485	/		
Network	Ethernet	RJ45		
	Protocols	TCP/IP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP, NTP,UPnP,SMTP,IPv6,et		
	Onvif Protocol	Yes		
Compatiable with	XMEYE APP, NVR, NAS, Live Stream to 3rd party Using RTSP			
Others	Power	12V DC (Dual Voltage DC12V/AC24V Optional)		
	POE	Optional		
	Housing	Metal IP66		
	Humidity	10-85% RH		
	Operation Conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F)		
	Weight	800g		
	Product Size	Size: ∅ 109 x 91(H) mm		