



Model	NVRB032
System	
Main Processor	Hi3536C
Operating System	Embedded LINUX
Video	
Video Input (IP)	8*4K/32*5M/32*1080P
Output	1ch VGA, 1ch HDMI HD output
Video Compression	H.265+/H.265/H.264
Display Quality	Max:4K
Playback Quality	4K/5M/1080P
Motion Detection	Support
Audio	
Input/Output	1/1
Audio Compression Standard	G.711A
Record & Playback	
Recording Mode	Manual>Alarm>Dynamic Detection>Timing
Local Playback	1*4K/2*5M/4*1080P
Search Mode	Search by Time/Calendar/Event/Channel
Storage & Backup Mode	
Record Storage	HDD 、 Network
Backup Mode	Network backup, USB hard disk, USB burner, SATA burner
Output	
Video Output	1ch VGA,1ch HDMI HD output
Network Interface	1*RJ45 10M/100M/1000M Adaptive Ethernet port
USB Interface	2*USB2.0 port
Hard Disk	1 or 2 SATA(Up to 8TB for each)
other	
Power Supply	12V4A
Power Consumption	<10W(Without HDD)
Work Environment	Temperature:0℃-+55℃ , Humidity:10%—90%RH , Atm:86kpa—106kp
Weight	2kg(without HDD)